

VRC4G0-0S HD IP 4G Rapid Deployment Dome PTZ Camera with Solar Panel



Description:

Portable 4G HD PTZ camera is a comprehensive function, easy to carry wireless video emergency command integration products, ultra-high equipment integration, built-in high-performance lithium battery pack, equipped with HD sound quality acousto-optic alarm, waterproof and shockproof features, can meet the special requirements of temporary distribution control and

rapid installation. Perform a task or job can quickly when installing equipment temporarily in the position of the need to monitor or adsorption on the vehicle directly, easy to equipment will be removed at the end of the task,

Application:

Applicable to the field of law enforcement, investigation, security protection, emergency command, emergency repair, patrol management, and other industry applications, such as public security, traffic police, fire protection, highways, urban management, traffic, railway, courts, prisons, forestry, electric power, water conservancy, environmental protection etc.

Features:

- 1080 HD video, H.264/ H.265 video encoding, double code stream
- Support trip wire, delimit area to enter warning area, move detection function
- Support sound and light alarm, voice, alarm sound can be set
- Support 4G all-network communication with built-in WIFI
- Support GPS position function.
- Support TF card local storage, maximum support 256G
- 360-degree omnidirectional head
- Support GB 28181 platform
- Integrated design, the bottom of the configuration of high suction magnet, fast installation
- Large capacity lithium battery power supply, working hours >8 hours
- LCD display for showing the battery capacity.
- Built in Bluetooth module. Support Bluetooth intercom.

Specifications:

| Items | | Description |
|----------------------|---|---|
| Video | Video compressed format | H.264 /H.265 |
| | Double stream | Support |
| | The resolution of the | 1080P/720P/D1 |
| | Preview function | Live video, video preview |
| Audio | Intercom partner | Optional |
| Storage | The local store | 1 TF card, Max. 256G |
| The wireless network | 4G/3G | Built-in 4G all-network communication module, compatible downward |
| | WIFI | Built-in WIFI module supports 802.11b/g/n |
| Extension interface | RJ45 network interface, RS485, charging interface | |
| Camera | Sensor type | 1/2.8" Progressive Scan CMOS |
| | Network protocol | IPv4, TCP/IP, UDP, HTTP, RTP/RTCP/RTSP/RTMP, FTP, UPnP, DDNS, NTP, IGMP, ICMP |
| | Signal system | PAL/NTSC |
| | Minimum illumination | Color: 0.05Lux @ (F1.6, AGC ON) Black and white: 0.01Lux @(F1.6, AGC ON) |
| | Day night mode | ICR infrared filter type |
| | The resolution of the | 1920*1080 1280*720 D1 |
| | The white balance | Automatic 1/ automatic 2/ indoor/outdoor/manual/sodium lamp/fluorescent lamp |
| | 3D noise reduction | Support |
| | Optical variable times | 30X |
| | Infrared | 60 meters |
| PTZ Camera | PTZ Agreement | PELCO-D/P |
| | Horizontal rotation Angle | 360° |
| | Vertical rotation Angle | -15°~90° |
| | Preset point | 256 |

| | | |
|-----------------------|------------------------|---|
| The power supply | The battery | 10000mah |
| | The charging time | 4 hours |
| | Work hours | 8 hours |
| | Solar panel | 2*50W total 100W |
| Sound and light alarm | Color of warning light | Red, yellow, blue and green are available |
| | The biggest DB | 120 db (a) |
| | Alarm sound | Voice can be set, with 9 standard options |
| | Tone \ volume | Remote control |
| Size | The host | 160*210mm |
| Weight | | Net Weight:3kg |
| | | Gross Weight:7.5kg |

Standard accessories: IP67 protection box / triangle bracket / tray / charger/ X1Composite airline X1

